

TED DUCT TAPE 50m x 48mm

- Polyethylene with textile fiber
- Non-sticky sides
- Good weatherability
- Good sealing properties
- High conformability
- Excellent workability
- Thick Adhesive
- Strong Webbed Backing
- Good moisture and chemical resistant
- Color: Gray



Properties	Value	Test Method
Total Thickness	0.2mm	IEC 60454-2§4
Tensile Strength	47 N/cm	IEC 60454-2§8
Elongation	19%	IEC 60454-2§8
Adhesion to Steel	5.8 N/cm	IEC 60454-2§11
Adhesion to Backing	1.42 N/cm	IEC 60454-2§11
Mesh -Number of Fibers-	70	IEC 60454-2§17
Low Temperature Properties	-10°C - No Degradation	IEC 60454-2§9
Maxim Operating Temperature	90°C	IEC 60454-2§21
Flamability	Flame Retardant	IEC 60454-2§19

More Info			
Model	TED10DuctTape	TED20DuctTape	TED50DuctTape
Tape Characteristics	48mm x 10m	48mm x 20m	48mm x 50m
Inner Diameter (mm)	72	72	72
Rolls/Box	60	60	60
Box Dimensions DxWxH (mm)	360 x 310 x 213	360 x 300 x 213	360 x 310 x 213
Net / Gross Weight (kg)	11/12	14/15	17/18
Color	Grey		
Application Guide	The Tape Should Be Applied On A Dry And Clean Surface Apply The Tape With A Moderate Tension And An Overlap Of 50%		

Due to continuous product improvements, program specifications are subject to change without notice