

UPS 1100VA Online Extended

- Automatic recharge
- Generator compatible
- Pure Sine Wave Output
- Protection for overload
- Interruptible buzzer alarm
- Battery (12V) not included
- LCD & 8 Status LED Display
- Smart battery management
- High Reliability Microprocessor
- Heavy duty cooper transformer
- AVR (automatic voltage regulator)
- Auto restart while AC is recovering
- External battery 12V maximum 300A
- 5 Steps power indicator & 5 Steps charging indicator
- Excellent performance for motor loading like fan and small pumps



Specifications	
Model	TED1100AM
Power (VA/W)	1100VA / 700W
Input	
Voltage Range	155V ÷ 265V AC
Frequency Range	45Hz ÷ 65Hz
Output	
AC Voltage Regulation (Batt. Mode)	220V ± 4% AC
Frequency Range (Batt. Mode)	50Hz ±0.05%
Waveform / Power factor	Pure Sine Wave / 0.8
Specifications	
Battery Charging	10A
Output Receptacle	2 x Schuko CEE 7/3
Operating Humidity/Temperature	10 - 90% / -10 + 40°C
Noise (dB) at 1m Distance	< 56 dB at full load
Class Protection	IP20
Dimension D x W x H (mm)	145 x 225 x h170
Net Weight (kg)	5.5

*Due to continuous product improvements, program specifications are subject to change without notice.