

Stabilizer TED WALL 500-1000VA

- Super slim wall mount design, compact size and space saving.
- Zero cross transfer technology integrated, longer operating life.
- High efficiency ultra slim toroidal transformer
- Full protections such as over voltage, under voltage, overload, over temperature, short circuit.
- Selectable Delay Time
- Digital display: input / output voltage, load rate, protection warnings, delay time
- CE / RoHS2.0 certified.



Specifications

Model	TED WALL 500VA	TED WALL 1000VA
Power	300W	600W
Input		
Voltage / Frequency Range	150-270V AC / 45-65Hz	
Input Connection	Schuko Power Cord	
Output		
Voltage / Frequency Range	230V +/- 4-5% AC / 50Hz	
Output Receptacle	2x Schuko	
Waveform / Power Factor	Pure Sine Wave / 0.6	
Efficiency	98%	
Delay Time	6s	
General Characteristics		
Protection	Over voltage / Under voltage / Overload / Overheat / Short-circuit / Surge	
Ingress Protection	IP20	
Noise level	<20dB at 1m distance with full load	
Dimensions DxWxH	175 x 72 x 300 mm	
Net Weight	2.63 kg	3.18 kg
Operating Humidity	10-90% non-condensing	
Operating Temperature	-15°C ~ + 40°C	